REFRICA GROUP

REFRICA · FRITECNO · FRINCO

Trocknungsanlagen / *Dryers*

Für wurst

For cured products

Früher war der Trocknungsprozess vollständig vom Wetter abhängig. Bei einer geringen Produktion erwies sich dieser Faktor als nicht allzu problematisch. Erst als die handwerkliche Herstellung auf die industrielle Produktion umgestellt wurde, stellte sich folgendes Problem: Um alle Märkte hinreichend versorgen zu können, musste die Produktion gesteigert werden. Dies erschwerte die Sicherstellung einer gleichbleibenden Qualität der Pökelerzeugnisse. Zu diesem Zeitpunkt entschieden wir uns, all unsere Energie darauf zu verwenden, unseren Kunden die beruhigende Gewissheit zu vermitteln, dass sie von nun an nicht mehr von den konstanten Wetterschwankungen abhängig waren.

In the past, the curing process was entirely at the mercy of weather conditions. This factor was not much of a problem as long as production was low. However, problems started to arise when we shifted from traditional production to industrial manufacturing. Production increased to keep up with market demand which in turn made it difficult to control the homogeneity of products to be cured. Then was when we decided to dedicate all our efforts to offering our clients a solution that did not depend on unstable weather conditions but rather offered peace of mind and thus be able to ensure the desired production capacity and homogeneity in and between batches of product.

Cámaras de Descongelación · *Thawing Rooms* | **Cámaras maduración** · *Aging Chambers* | **Túneles Congelación** · *Freezing Tunnels*
Salas Blancas · *Clean Rooms* | **Enfriadora NH_3** · *NH_3 - Chiller* | **Centrales de Frío** · *Refrigeration Plants* | **Control y Gestión** · *Control & Management*

24h **24 Stunden am Tag und 365 Tage im Jahr**
24 hours a day and 365 days a year

Verantwortung Refrica
Refrica responsibility

5.0 **Refrica und Industrie 5.0**
Refrica and Industry 5.0

Technologie im Dienst des besten Klimas

Je nach den Anforderungen des Kunden können die Anlagen eigenständige oder zentralisierte Geräte sein. Es werden indirekte (Propylenglykol) oder direkte (NH3 oder Freon (HFC)) Kühlmittel eingesetzt.

Technology at the service of the best climate

Based on the client's needs, installations can be automatic or centralized. Refrigerants may be indirect (propylene glycol) or direct (NH_3) or Freon (HFC).



Modell / *Model*	Länge / *Lenght*	Tiefe / *Depth*	Hoch / *High*	Kälteleistung *Refrigeration Power*
ARV-40	3870 mm / 152,36 in	1435 mm / 56,49 in	2614 mm / 102,91 in	225 kW
ARV-30	2770 mm / 109,05 in	1435 mm / 56,49 in	2495 mm / 98,23 in	150 kW
ARV-20	1370 mm / 53,93 in	1215 mm / 47,83 in	2495 mm / 98,23 in	75 kW
ARV-10	1670 mm / 65,75 in	995 mm / 39,17 in	2195 mm / 86,42 in	50 kW
ARV-5	1370 mm / 59,94 in	775 mm / 30,5 in	2195 mm / 86,42 in	25 kW

Wir passen die Ausrüstung an die spezifischen Bedürfnisse des Kunden an, je nach den Dimensionen und Besonderheiten der Installation *

We adapt equipment to the client's specific needs in terms of the dimensions and characteristics of the installation

Refrica

Ctra. Nacional IIa, 47 · 17458 Fornells de la Selva · Girona · Spain

+34 972 476 253 · refrica@refrica.com · www.refrica.com